

CLASSIC HOT ROD BLACK ACTIVATOR-SLOW

#40216-1/2 PINT



SECTION I - MANUFACTURERS INFORMATION

PRODUCT NUMBER: 40216
PRODUCT NAME: Classic Hot Rod Black Activator Slow
DATE PREPARED: 02.07.2019
REVISION DATE: 06.14.2019

COMPANY: EXCEL AUTOBODY PRODUCTS
ADDRESS: 2921 SYENE ROAD
CITY: MADISON, WI 53713
PHONE: (800) 957-0848
EMERGENCY PHONE: (800) 424-9300

SECTION II - HAZARDOUS INGREDIENTS

CLASSIFICATION:

Flammable Liquids	Category 2
Acute Toxicity, Inhalation	Category 4
Sensitization, respiratory	Category 1
Sensitization, skin	Category 1
Hazardous to the aquatic environment, long term hazard	Category 3
OSHA defined hazards	Not Classified

SIGNAL WORD: **DANGER!**

PICTOGRAMS:



HAZARD STATEMENTS:

H226	Flammable liquid and vapor
H315	Causes skin irritation
H320	Causes eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H341	Suspected of causing genetic defects
H350	May cause cancer
H361	Suspected of damaging fertility or the unborn child
H373	Causes damage to organs through prolonged or repeated exposure

Excel Products US, Inc.,
2921 Syene Rd, Madison, WI 53713
Tel: (800) 957-0848 Fax: (608) 274-5313
Email: marketing@excelproducts.net
Website: www.excelproducts.net

CLASSIC HOT ROD BLACK ACTIVATOR-SLOW

#40216-1/2 PINT

PRECAUTIONARY STATEMENTS:

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surface - No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/light/equipment, etc.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P271	Use only outdoors or in a well-ventilated are.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P281	Use personal protective equipment as required.
P302+352	IF ON SKIN: Wash with soap and water.
P303+361+353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so - continue rinsing.
P308+313	IF exposed or concerned: get medical advice/attention.
P312	Call a POISON CENTER or a doctor/physician if you feel unwell.
P314	Get medical advice/attention if you feel unwell.
P332+313	If skin irritation occurs: get medical advice/attention.
P337+313	If eye irritation persists get medical advice/attention.
P362	Take off contaminated clothing and wash before reuse.
P370+378	In case of fire: Usedry sand, dry chemical, or alcohol-resistant foam for extinction.
P403+233	Store in a well ventilated place. Keep container tightly closed.
P403+235	Store in a well ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container to an approved waste disposal plant.

SECTION III - COMPOSITION/INFORMATION ON INGREDIENTS

The precise composition of this product is proprietary information. In the event of a medical emergency, a complete disclosure will be provided to medical personnel.

MATERIAL:

Parachlorobenzotrifloride
Flexamethylene Diisocyanate
Ethylhexyl Acetate 2

CAS #:

98-56-6
28182-81-2
103-09-3

WEIGHT %:

45-65
30-50
5-10



CLASSIC HOT ROD BLACK ACTIVATOR-SLOW

#40216-1/2 PINT

SEE SECTIONS VIII, XI, XII FOR TOXICOLOGICAL INFORMATION.

SECTION IV - FIRST AID MEASURES

CONTACT WITH EYES AND SKIN: Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops and persists.

INHALATION: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth to mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one way valve or other proper respiratory medical device. If experiencing respiratory symptoms call a POISON CENTER or doctor physician.

INGESTION: If swallowed. Do not induce vomiting. Seek immediate medical attention.

GENERAL INFORMATION: Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

SECTION V - FIREFIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA: Water fog, foam, dry chemical powder, or carbon dioxide extinguisher. Sand or earth may be used for small fires only.

INSUITABLE EXTINGUISHING MEDIA: Water. Do not use water jet as an extinguisher, as this will spread the fire.

SPECIFIC HAZARDS ARISING FROM THE CHEMICAL: Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.

SPECIAL FIRE FIGHTING PROCEDURES: In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Use standard firefighting procedures and consider the hazards of other involved materials. Self contained breathing apparatus and full protective clothing must be worn in case of fire.

GENERAL FIRE HAZARDS: Highly flammable liquid vapor.

SECTION VI - ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS (protective equipment and emergency procedures): Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean up. Avoid inhalation of vapors and spray mists. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.



CLASSIC HOT ROD BLACK ACTIVATOR-SLOW

#40216-1/2 PINT

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP:

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent product from entering drains. Following product recovery, flush area with water. Absorb with earth, sand or other non combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

ENVIRONMENTAL PRECAUTIONS: Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases. Use appropriate containment to avoid environmental contamination.

SECTION VII - HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING: Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion proof general and local exhaust ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulations liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, crating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non sparking tools and explosion proof equipment. Avoid inhalation of vapors and spray mists. Avoid contact with eyes, skin, and clothing. Use only outdoors or in a well ventilated area. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

For additional information on equipment bonding and grounding, refer to the Canadian Electrical Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents or National Fire Protection Association (NFPA) 77, Recommended Practice on Static Electricity or National Fire Protection Association (NFPA) 70, National Electrical Code.

CONDITIONS FOR SAFE STORAGE (Including any incompatibilities): Keep away from heat, sparks and open flame. Prevent electrostatic charge build up by using common bonding and grounding techniques. Eliminate sources of ignition. Avoid spark promoters. Ground bond container and equipment. These alone may be insufficient to remove static electricity. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

SECTION VIII - PRECAUTIONS TO CONTROL EXPOSURE / PERSONAL PROTECTION

Occupational exposure limits: No exposure limits noted for ingredient(s).

Biological limit values: No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls: Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash fountain and emergency showers are recommended.

Individual protection measures (such as protective equipment): **Eye/face protection:** Chemical respirator with organic vapor cartridge and full facepiece. **Hand protection:** Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier. **Respiratory protection:** Chemical respirator with organic vapor cartridge and full facepiece. **Other:** Wear appropriate chemical resistant clothing.

Thermal hazards: Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations: when using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.



CLASSIC HOT ROD BLACK ACTIVATOR-SLOW

#40216-1/2 PINT

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:	Colorless liquid
ODOR:	Solvent
ODOR THRESHOLD:	Not Available
pH@25°C:	Not Applicable
MELTING/FREEZING POINT:	-112°F (-80°C)
INITIAL OILING POINT:	282.74°F (139.3°C)
FLASHPOINT:	55.4°F (13.0°C)
EVAPORATION RATE:	Not available
FLAMMABILITY (Solid, Gas):	Not Applicable
AUTO-IGNITION TEMPERATURE:	515°F (268.33°C)
DECOMPOSITION TEMPERATURE:	Not Available
BOILING RANGE:	134 - 137°F
EVAPORATION RATE:	Not Availbale
LOWER FLAMMABLE LIMIT:	Not Available
UPPER FLAMMABLE LIMIT:	Not Available
LOWER EXPLOSIVE LIMIT:	Not Available
UPPER EXPLOSIVE LIMIT:	Not Available
VAPOR PRESSURE:	- #]EV
VAPOR DENSITY (air=1):	Not Available
RELATIVE DENSITY:	Not Available
VISCOSITY:	Not Available
SOLUBILITY (water):	Not Available
PARTITION COEFFICIENT (n-octanol water)	Not Available
DENSITY:	Not Available
FLAMMABILITY CLASS:	1.27 g cm3 Flammable IB
PERCENT VOLATILE:	58.19 v/v % By Volume 62 w/w % By Weight
SPECIFIC GRAVITY:	1.27
VOC(weight %):	0.78 lb/gal (Actual VOC-With Water With Exempts) 1.49 lb/gal (Regulatory VOC-Less Water Less Exempts) 94.01 g/L (Actual VOC-With Water With Exempts) 178.70 g/L (Regulatory VOC-Less Water Less Exempts)

SECTION X - STABILITY AND REACTIVITY

REACTIVITY: The product is stable and non reactive under normal conditions of use, storage and transport.

CHEMICAL STABILITY: Material is stable under normal conditions.

POSSIBILITY OF HAZARDOUS REACTIONS: Hazardous polymerization does not occur.

CONDITIONS TO AVOID: Heat, sparks, open flames an other ignition sources. Avoid temperatures exceeding the flash point.

Contact with incompatible material.

HAZARDOUS DECOMPOSITION/BYPRODUCTS: No hazardous decomposition products are known.

INCOMPATIBILITIES: Strong oxidizing agents.

CLASSIC HOT ROD BLACK ACTIVATOR-SLOW

#40216-1/2 PINT

SECTION XI - TOXICOLOGICAL INFORMATION

LIKELY ROUTE OF EXPOSURE

INHALATION: Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

SKIN CONTACT: May cause an allergic skin reaction.

EYE CONTACT: Direct contact with eyes may cause temporary irritation.

INGESTION: Expected to be a low ingestion hazard.

SYMPTOMS (related to the physical, chemical, and toxicological characteristics): Difficulty in breathing. May cause an allergic skin reaction. Dermatitis. Rash.

INFORMATION ON TOXOLOGICAL EFFECTS:

Acute toxicity: Harmful if inhaled. May cause an allergic skin reaction.

Material: CAS LD50

Ethylexyl Acetate 2 103 0 3 Oral: 3 g kg (rat)

*estimates for product may be based on additional component data not shown.

Skining corrosion/irritation: Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation: Direct contact with eyes may cause temporary irritation.

Respiratory sensitization: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin sensitization: May cause an allergic skin reaction.

Germ cell mutagenicity: No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity: This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not listed.

Reproductive toxicity: This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity (single exposure): Not classified.

Specific target organ toxicity (repeated exposure): Not classified.

Aspiration hazard: Not an aspiration hazard.

SECTION XII - ECOLOGICAL INFORMATION

ECOTOXICITY: Harmful to aquatic life with long lasting effects.

PERSISTENCE AND DEGRADABILITY: No data is available on the degradability of this product.

MOBILITY (in soil): No data available.

BIOACCUMULATION: No data available.

SECTION XIII - WASTE DISPOSAL CONSIDERATIONS

Disposal instruction: Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with local/regional/national/international regulations.

Local disposal regulation: Dispose in accordance with all applicable regulations.

Hazardous waste code: The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues/unused products: Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions.)

Contaminated packaging: Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

(*endocrine disruption, global warming potential) are expected from this component.



CLASSIC HOT ROD BLACK ACTIVATOR-SLOW

#40216-1/2 PINT

SECTION XIV - TRANSPORT INFORMATION

The following transportation information is provided based on the manufacturer's interpretation of shipping regulations. Each shipper is responsible for identifying, naming, marking, and labeling prior to offering for transport.

DOT:

Packaging exceptions: 150

Packaging non bulk: 173

Packaging bulk: 242

IATA:

UN NUMBER:	UN1263
PROPER SHIPPING NAME:	Paint related material (including paint thinning or reducing compounds)
TRANSPORT HAZARD CLASS:	3
PACKAGING GROUP:	III

ENVIRONMENTAL HAZARDS:	No.
ERG CODE:	3L
SPECIAL PRECAUTIONS (for user):	Read safety instruction, SDS and emergency procedures before handling.
OTHER SHIPPING INFORMATION:	Passanger and cargo aircraft allowed. Cargo aircraft only is allowed.

IMDG:

UN NUMBER:	UN1263
PROPER SHIPPING NAME:	Paint related material (including paint thinning or reducing compounds)
TRANSPORT HAZARD CLASS:	3
PACKAGING GROUP:	II
ENVIRONMENTAL HAZARDS (marine pollutant):	No.
EmS:	F-E, S-E
SPECIAL PRECAUTIONS (for user):	Read safety instruction, SDS and emergency procedures before handling.

SECTION XV - REGULATORY INFORMATION

US FEDERAL REGULATIONS: This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communicaiton Standard, 29 CFR 1910.1200. One or more component are not listed on TSCA

TSCA section 12(b) Export Notification (40 CFR 707, Subpt. D): Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4): Not listed.

SARA 304 Emergency release notification: Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA):

Hazard Categories:

Immeidate Hazard-Yes

Delayed Hazard-No, Fire Hazard-Yes, Pressure Hazard-No

Reactivity Hazard-No

SARA 302 Extremely hazardous substance: Not listed.

SARA 311/312 hazardous chemical: No.

SARA 313 (TRI reporting): Not regulated.

OTHER FEDERAL REGULATIONS:

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) Listed: Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130): Not regulated.

Safe Drinking Water Act (SWDA): Not regulated

**CLASSIC HOT ROD BLACK ACTIVATOR-SLOW**

#40216-1/2 PINT

US. STATE REGULATIONS:

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100: Not listed.**US. Massachusetts RTK-Substance List:** Ethylhexyl Acetate 2 (CAS 103-09-3)**US. New Jersey Worker and Community Right-to-Know Act:** Not listed.**US. Pennsylvania Worker and Community Right-to-Know Law:** Ethylhexyl Acetate 2 (CAS 103-09-3)**US. Rhode Island RTK:** Not regulated.**US. California Proposition 65:** California Safe Drinking Water and Toxic Enforcement Act of 1986 (proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

INTERNATIONAL INVENTORIES:

Country(s) or Region:	Inventory name:	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European inventory of Existing commercial Chemical Substances (EINECS)	No
Europe	European List of Notified chemical Substances (ELINCS)	No
Japan	Inventory of Existing and new Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

*A "yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s). A "no" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

CALIFORNIA PROPOSITION 65:

This product contains no chemicals known to the state of California to cause cancer, birth defects or other reproductive harm. For more information go to www.p65warnings.ca.gov

SECTION XVI - OTHER INFORMATION

HMIS Health:	2
HMIS Flammability:	3
HMIS Reactivity:	0

DISCLAIMER: WARNING! KEEP THIS AND ALL PAINT RELATED PRODUCTS OUT OF THE REACH OF CHILDREN! The information contained in this SDS is based on data from sources considered to be reliable but we do not guarantee the accuracy or completeness thereof. We urge each customer or recipient of this SDS to study it carefully to become aware of and understand the hazards associated with this product. The reader should consider consulting reference works or individuals who are experts in ventilation, toxicology, or fire prevention as necessary or appropriate to use and understand the data in this SDS.

Excel Products US, Inc.,
2921 Syene Rd, Madison, WI 53713
Tel: (800) 957-0848 Fax: (608) 274-5313
Email: marketing@excelproducts.net
Website: www.excelproducts.net