

SAFETY DATA SHEET

1. Identification

Product identifier Speed Clear

Product code 810

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name PBE Jobbers Warehouse
Address 2921 Syene Rd
Madison, WI 53713

Telephone 608-274-8797

Emergency phone number EMERGENCY 24 Hrs. 800-424-9300ChemTrec

Physical hazards	Flammable liquids	Category 2
Health hazards	Acute toxicity, dermal	Category 4
	Acute toxicity, inhalation	Category 3
	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Sensitization, skin	Category 1
	Carcinogenicity	Category 2
	Reproductive toxicity (the unborn child) Specific target organ toxicity, single exposure	Category 2 Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 1
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 2

2. Hazard(s) identification
Hazardous to the aquatic environment, long-term hazard Category 2

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Highly flammable liquid and vapor. Harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction Causes serious eye irritation. Toxic if inhaled May cause drowsiness or dizziness. Suspected of causing cancer Suspected of damaging the unborn child. Causes damage to organs through prolonged or repeated exposure. Toxic to aquatic life Toxic to aquatic life with long lasting effects.

Precautionary statement	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood Keep away from heat/sparks/open flames/hot surfaces - No smoking Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.
Prevention	
Response	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor. If skin irritation or rash occurs: Get medical advice/attention If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to extinguish. Collect spillage.
Storage	Store in a well-ventilated place. Keep container tightly closed Store in a well-ventilated place Keep cool. Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations. Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion. 63.13% of the mixture consists of component(s) of unknown acute dermal toxicity. 54.12% of the mixture consists of component(s) of unknown acute inhalation toxicity. 60.34% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment 59.82% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.
Hazard(s) not otherwise classified (HNOC)	
Supplemental information	

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Glycol Ether PM Acetate		108-65-6	20 - < 40
Methyl Acetate		79-20-9	10 - < 30
Xylene		1330-20-7	10 - < 30
Acetone		67-64-1	5 - < 10
Ethylbenzene		100-41-4	5-< 10
N-Butyl Acetate		123-86-4	5 - < 10
Bis(1, 2, 2, 6, 6-Pentamethyl-4-piperidinyl) Sebacate		41556-26-7	0< 5
Dibutyltin Dilaurate		77-58-7	0<5
Toluene		108-88-3	0< 5
Other components below reportable levels			1 - < 3

4. **First-aid measures**
Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device Call a POISON CENTER or doctor/physician Remove contaminated clothing immediately and wash skin with soap and water. Get medical advice/attention if you feel unwell. In case of eczema or other skin disorders. Seek medical attention and take along these instructions. Wash contaminated clothing before reuse. Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do Continue rinsing. Get medical attention if irritation develops and persists. Rinse mouth. Get medical advice/attention if you feel unwell
Skin contact	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation May cause redness and pain May cause an allergic skin reaction Dermatitis Rash Prolonged exposure may cause chronic effects.
Eye contact	
Ingestion Most important symptoms/effects, acute and delayed	

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital Keep victim warm. Keep victim under observation. Symptoms may be delayed

General information

Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Alcohol resistant foam. Water fog. Carbon dioxide (CO₂). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures.

This liquid may accumulate static electricity when filling property grounded containers Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Specific methods

General fire hazards

Use standard firefighting procedures and consider the hazards of other involved materials.

Highly flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent product from entering drains. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground Inform appropriate managerial or supervisory personnel of all environmental releases. Use appropriate containment to avoid environmental contamination

7. Handling and storage

Precautions for safe handling Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke Pregnant or breastfeeding women must not handle this product. Should be handled in dosed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment Wash hands thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Observe good industrial hygiene practices

For additional information on equipment bonding and grounding, refer to the Canadian Electrical Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77. "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code".

Conditions for safe storage. Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge **including any incompatibilities** build-up by using common bonding and grounding techniques. Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container Store in a well-ventilated place Keep in an area equipped with sprinklers Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Acetone (CAS 67-64-1)	PEL	2400 mg/m ³ 1000 ppm
Dibutyltin Dilaurate (CAS 77-58-7)	PEL	0.1 mg/m ³
Ethylbenzene (CAS 100-41-4)	PEL	435 mg/m ³
Methyl Acetate (CAS 79-20-9)	PEL	100 ppm 610 mg/m ³
N-Butyl Acetate (CAS 123-86-4)	PEL	200 ppm 710 mg/m ³
Xylene (CAS 1330-20-7)	PEL	150 ppm 435 mg/rr ³ 100 ppm

US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value
Toluene (CAS 108-88-3)	Ceiling TWA	300 ppm 200 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
Acetone (CAS 67-64-1)	STEL TWA	750 ppm 500 ppm
Dibutyltin Dilaurate (CAS 77-58-7)	STEL TWA	0.2 mg/m ³ 0.1 mg/m ³

US. ACGIH Threshold Limit Values

	Type	
Ethylbenzene (CAS 100-41-4)	TWA	20 ppm
Methyl Acetate (CAS 79-20-9)	STEL	250 ppm
N-Butyl Acetate (CAS 123-86-4)	TWA	200 ppm
	STEL	200 ppm
Toluene (CAS 108-88-3)	TWA	150 ppm
	TWA	20 ppm
Xylene (CAS 1330-20-7)	STEL	150 ppm
	TWA	100 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Acetone (CAS 67-64-1)	TWA	590 mg/m3
		250 ppm
Dibutyltin Dilaurate (CAS 77-58-7)	TWA	0.1 mg/m3
Ethylbenzene (CAS 100-41-4)	STEL	545 mg/m3
		125 ppm
	TWA	435 mg/m3
		100 ppm
Methyl Acetate (CAS 79-20-9)	STEL	760 mg/m3
		250 ppm
	TWA	610 mg/m3
		200 ppm
N-Butyl Acetate (CAS 123-86-4)	STEL	950 mg/m3
		200 ppm
	TWA	710 mg/m3
		150 ppm
Toluene (CAS 108-88-3)	STEL	560 mg/m3
		150 ppm
	TWA	375 mg/m3
		100 ppm

US. Workplace Environmental Exposure Level (WEEL) Guides

Components	Type	Value
Glycol Ether PM Acetate (CAS 108-65-6)	TWA	50 ppm

logical limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	50 mg/l	Acetone	Urine	*
Ethylbenzene (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in unne	*
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol. with hydrolysis	Creatinine in unne	*
		Toluene	Urine	*
		Toluene	Blood	*
Xylene (CAS 1330-20-7)	1.5 g/g	Methyhippuric acids	Creatinine in unne	*

■ - For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

Dibutyltin Dilaurate (CAS 77-58-7)

Can be absorbed through the skin.

Glycol Ether PM Acetate (CAS 108-65-6)

Can be absorbed through the skin

Toluene (CAS 108-88-3)

Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Dibutyltin Dilaurate (CAS 77-58-7)

Skin designation applies.

Toluene (CAS 108-88-3)

Skin designation applies

US - Tennessee OELs: Skin designation

Dibutyltin

Dilaurate (CAS 77-58-7)

Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Dibutyltin Dilaurate (CAS 77-58-7)

Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

Dibutyltin Dilaurate (CAS 77-58-7)

Can be absorbed through the skin.

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection

Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection

Hand protection

Wear appropriate chemical resistant gloves Suitable gloves can be recommended by the glove supplier.

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. Chemical

Other

respirator with organic vapor cartridge and full facepiece Wear appropriate thermal protective clothing,

Respiratory protection

when necessary.

Thermal hazards

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and

General hygiene considerations

protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state

Liquid.

Form

Liquid

Color

Colorless

Odor

Solvent.

Odor threshold

Not available.

PH

Not available.

Melting point/freezing point

-144.4 °F (-98 °C) estimated

Initial boiling point and boiling range

132.89 °F (56.05 °C) estimated

Flash point

-4.0 °F (-20.0 °C) estimated

Evaporation rate

Not available

Flammability (solid, gas)

Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower (%)

1.2 % estimated

Flammability limit - upper (%)

16 % estimated

Explosive limit - lower (%)

Not available.

Explosive limit - upper (%)

Not available.

Vapor pressure

91.13 hPa estimated

Vapor density	Not available.
Relative density	Not available.
Solubility(ics)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	797 °F (425 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	0.88 g/cm ³ estimated
Flammability class	Flammable IB estimated
Specific gravity	0.88 estimated
VOC (Weight %)	2.83 lb/gal (Actual VOC - With Water With Exempts) 4.05 lb/gal (Regulatory VOC - Less Water Less Exempts) 338.80 g/l (Actual VOC - With Water With Exempts) 484.75 g/l (Regulatory VOC - Less Water Less Exempts)

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials
Incompatible materials	Strong acids. Strong oxidizing agents. Nitrates. Halogens.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information **Information on likely routes of exposure**

Inhalation	Toxic if inhaled. May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting.
Skin contact	Harmful in contact with skin. Causes skin irritation May cause an allergic skin reaction
Eye contact	Causes serious eye irritation.
Ingestion	Expected to be a low ingestion hazard.
Symptoms related to the physical, chemical and	Headache. May cause drowsiness and dizziness. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May

toxicological characteristics cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Components	Toxic if inhaled. Harmful in contact with skin. Narcotic effects. May cause an allergic skin reaction	
	Species	Test Results

Acetone (CAS 67-64-1)

Acute

Dermal

LD50

Inhalation

LC50

Rabbit

20000 mg/kg

20 ml/kg

Rat

76 mg/l, 4 Hours

50.1 mg/l, 8 Hours

Oral

LD50

Mouse

3000 mg/kg

Rabbit

5340 mg/kg

Components	Species	Test Results
Dibutyltin Dilaurate (CAS 77-58-7)	Rat	5800 mg/kg
<u>Acute</u>		
Oral		
LD50	Rat	175 mg/kg
Ethylbenzene (CAS 100-41-4)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	17800 mg/kg
Oral		
LD50	Rat	3500 mg/kg
Methyl Acetate (CAS 79-20-9)		
<u>Acute</u>		
Oral		
LD50	Rabbit	3.7 g/kg
N-Butyl Acetate (CAS 123-86-4)		
<u>Acute</u>		
Inhalation		
LC50	Wistar rat	160 mg/l. 4 Hours
Oral		
LD50	Rat	14000 mg/kg
Toluene (CAS 108-88-3)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	12124 mg/kg 14.1 ml/kg
Inhalation		
LC50	Mouse	5320 ppm. 8 Hours 400 ppm, 24 Hours
	Rat	26700 ppm. 1 Hours 12200 ppm, 2 Hours 8000 ppm. 4 Hours
Oral		
LD50	Rat	2.6 g/kg
Xylene (CAS 1330-20-7)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	>43 g/kg
Inhalation		
LC50	Mouse	3907 mg/l, 6 Hours
	Rat	6350 mg/l, 4 Hours
Oral		
LD50	Mouse	1590 mg/kg 3523 -
	Rat	8600 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Causes skin irritation.
Serious eye damage/eye irritation Causes serious eye irritation

Respiratory or skin sensitization**Respiratory sensitization**

Not a respiratory sensitizer.

Skin sensitization

May cause an allergic skin reaction.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity

Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

Ethylbenzene (CAS 100-41-4)

2B Possibly carcinogenic to humans.

Toluene (CAS 108-88-3)

3 Not classifiable as to carcinogenicity to humans.

Xylene (CAS 1330-20-7)

3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed

Reproductive toxicity

Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals. Suspected of damaging the unborn child.

Specific target organ toxicity - single exposure

May cause drowsiness and dizziness

Specific target organ toxicity - repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard**Chronic effects**

Not an aspiration hazard

Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects

12. Ecological information**Ecotoxicity**

Toxic to aquatic life with long lasting effects.

Components		Species	Test Results
Acetone (CAS 67-64-1)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	10294 - 17704 mg/l, 48 hours
Fish	LC50	Rainbow trout.donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours
Ethylbenzene (CAS 100-41-4)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	1.37 - 4.4 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	7.5 - 11 mg/l, 96 hours
Methyl Acetate (CAS 79-20-9)			
Aquatic			
Fish	LC50	Fathead minnow (Pimephales promelas)	295 - 348 mg/l, 96 hours
N-Butyl Acetate (CAS 123-86-4)			
Aquatic			
Fish	LC50	Fathead minnow (Pimephales promelas)	17 - 19 mg/l, 96 hours
Toluene (CAS 108-88-3)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	5.46 - 9.83 mg/l, 48 hours
Fish	LC50	Coho salmon.silver salmon (Oncorhynchus kisutch)	8.11 mg/l, 96 hours
Xylene (CAS 1330-20-7)			
Aquatic			
Fish	LC50	Bluegill (Lepomis macrochirus)	7.711 - 9.591 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown. **Persistence****and degradability** No data is available on the degradability of this product. **Bioaccumulative potential****Partition coefficient n-octanol / water (log Kow) Acetone -0.24**

Partition coefficient n-octanol / water (log Kow)

Dibutyltin Dilaurate	3.12
Ethylbenzene	3.15
Methyl Acetate	0.18
N-Butyl Acetate	1.78
Toluene	2.73
Xylene	3.12-3.2

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

Disposal instructions 13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Hazardous waste code

Dispose in accordance with all applicable regulations

Waste from residues / unused products

The waste code should be assigned in discussion between the user, the producer and the waste disposal company

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal

14. Transport information

The following transportation information is provided based on the manufacturer's interpretation of shipping regulations. Each shipper is responsible for identifying, naming, marking, and labeling prior to offering for transport.

DOT

UN number	UN1263
UN proper shipping name	Paint related material including paint thinning, drying, removing, or reducing compound (Macrynal SM 510 n/60lgv4, Tinuvin 292 HP)
Transport hazard class(es)	
Class	3
Subsidiary risk Label(s)	3
Packing group	II
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	149, B52, IB2, T4, TP1, TP8, TP28
Packaging exceptions	150
Packaging non bulk	173
Packaging bulk	242

IATA

UN number	UN 1263
UN proper shipping name	Paint related material (including paint thinning or reducing compounds) 3
Transport hazard class(es)	II
Class	No.
Subsidiary risk Packing group	ERG Code 3L
Environmental hazards	Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Other information Allowed.
Passenger and cargo aircraft	Allowed
Cargo aircraft only	Allowed

IMDG

UN number	UN 1263
UN proper shipping name	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)

Transport hazard class(es) Class

3

Subsidiary risk

Packing group

II

Environmental hazards

Marine pollutant

No.

EmS

F-E, S-E

Special precautions for user Read safety instructions. SDS and emergency procedures before handling.

Transport in bulk according to Not established.

Annex II of MARPOL 73/78 and the IBC Code

DOT



IATA; IMDG



Acetone (CAS 67-64-1)

Listed.

Ethylbenzene (CAS 100-41-4)

Listed.

Methyl Acetate (CAS 79-20-9)

Listed.

N-Butyl Acetate (CAS 123-86-4)

Listed.

Toluene (CAS 108-88-3)

Listed.

Xylene (CAS 1330-20-7)

Listed.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard. 29 CFR 1910.1200.

One or more components are not listed on TSCA.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated

CERCLA Hazardous Substance List (40 CFR 302.4)

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA) Hazard categories

Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard -

No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Xylene	1330-20-7	10 - < 30
Ethylbenzene	100-41-4	5 - < 10
Toluene	108-88-3	0 < 5

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Ethylbenzene (CAS 100-41-4)

Toluene (CAS 108-88-3)

Xylene (CAS 1330-20-7)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not regulated.

(SDWA)

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Acetone (CAS 67-64-1) 6532

Toluene (CAS 108-88-3) 6594

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1) 35 %WV

Toluene (CAS 108-88-3) 35 %WV

DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1) 6532

Toluene (CAS 108-88-3) 594

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Acetone (CAS 67-64-1)

Bis(1, 2, 2, 6, 6-Pentamethyl-4-piperidinyl) Sebacate (CAS 41556-26-7)

Ethylbenzene (CAS 100-41-4)

Toluene (CAS 108-88-3)

Xylene (CAS 1330-20-7)

US. Massachusetts RTK - Substance List Acetone (CAS 67-64-1)

Ethylbenzene (CAS 100-41-4)

Methyl Acetate (CAS 79-20-9)

N-Butyl Acetate (CAS 123-86-4)

Toluene (CAS 108-88-3)

Xylene (CAS 1330-20-7)

US. New Jersey Worker and Community Right-to-Know Act

Acetone (CAS 67-64-1)

Ethylbenzene (CAS 100-41-4)

Methyl Acetate (CAS 79-20-9)

N-Butyl Acetate (CAS 123-86-4)

Toluene (CAS 108-88-3)

Xylene (CAS 1330-20-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Acetone (CAS 67-64-1)

Ethylbenzene (CAS 100-41-4)

Methyl Acetate (CAS 79-20-9)

N-Butyl Acetate (CAS 123-86-4)

Toluene (CAS 108-88-3)

Xylene (CAS 1330-20-7)

US. Rhode Island RTK Acetone (CAS 67-64-1)

Ethylbenzene (CAS 100-41-4)

N-Butyl Acetate (CAS 123-86-4)

Toluene (CAS 108-88-3)

Xylene (CAS 1330-20-7)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance Ethylbenzene (CAS 100-41-4) Listed:

June 11, 2004

US - California Proposition 65 - CRT: Listed date/Developmental toxin

August 7. 2009

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)'
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

'A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Disclaimer

Our Company cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use The information in the sheet was written based on the best knowledge and experience currently available.